

Quiescent dewatering retains even the finest grit particles.

Technical Brochure - Product Profile

The Grit Snail® uses a slow moving cleated belt to gently escalate grit from the clarifier pool without re-suspending fine grit particles which will cause them to escape with the clarifier overflow.

Applications

- Grit dewatering for municipal WWTPs
- Dewateres grit output from a SlurryCup™, TeaCup®, or Grit King® unit
- Sludge dewatering or headworks dewatering applications
- Agricultural and industrial applications



Advantages

- Non-turbulent process retains the smallest grit particles
- Durable 304 or 316 stainless steel construction ensures a long product life
- Large clarifier with a low overflow rate provides sufficient time for grit to settle

How it Works

A washed grit slurry is discharged into the Grit Snail® clarifier. The clarifier is sized to provide sufficient area for particles as small as 75 micron to settle. Degritted effluent overflows a weir and goes on to the next process. The captured grit settles to the bottom of the clarifier and onto the belt. The slowly moving belt gently lifts accumulated grit from the clarifier bottom without re-suspending it, eliminating the potential for carry-over. The belt typically moves at 1-2 feet / minute which creates quiescent dewatering conditions.

The grit settles onto the stepped cleats and is gently lifted out of the clarifier. Dewatering begins as the grit and fine abrasives are quiescently raised from the clarifier pool. The dewatered abrasives are carried to the top of the Grit Snail®, where they are discharged into a container for disposal. The lined belt housing, stepped rubber belt cleats, and no metal-to-metal contact ensures long component life and minimal wear. The variable frequency drive adjusts belt speed to match changing grit loads.



SlurryCup™ / Grit Snail®
with optional access platform

Configurations

- The SlurryCup™ (or TeaCup®) / Grit Snail® system can either be used for headworks degritting or to de-grit concentrated slurry captured from a HeadCell® or a Grit King® separation system
- Multiple inlet and outlet arrangements are available to accommodate plant piping conditions
- The system can be provided with an optional maintenance access platform

Grit Snail® Performance

- Removes 95% of particles 75 microns and larger at the design flow rate when used with a Hydro washing system
- 60% total solids and less than 20% volatile solids when used with a SlurryCup™ or TeaCup®

Design Notes

- Large clarifier area allows even very fine grit to settle
- Slow moving belt eliminates grit carry over
- Belt housing is lined with abrasion resistant urethane for long service life

Capacity

- Dewatering capacity from 1-10 yd³/hr of grit
- Clarifier sizes from 48" to 96" square
- Belt widths from 6" to 57.5"
- The Grit Snail® can be configured to match most applications as the clarifier is sized for flow while the belt is sized for grit load

Visit hydro-int.com/GritSnail · email questions@hydro-int.com or call 866.615.8130 today to discover how the **Grit Snail** will save you money!



Offered in Australia and New Zealand by:
VoR
 ENVIRONMENTAL
 13-15 Aylesbury Street, Botany
 NSW 2019 Australia
 (t): +61 (02) 9695 1911
www.vor-env.com